

## TROFFER DOOR RETROFIT (TDR)

Linmore LED Labs Troffer Door Retrofit (TDR) is the ultimate and complete upgrade to troffer lighting. The TDR is both an aesthetic improvement clearly modernizing troffer lighting, and a serious energy play offering ultra-energy savings. The light engine of the TDR is Linmore's patent-pending URS Light Bar System combined with an external, dimmable driver. The amount of light, without glare, and the consistent distribution of light per watt of energy consumed is unmatched by any other troffer retrofit system. When the objective is to slash the energy costs of troffer lighting while upgrading the appearance, the Linmore TDR is the clear choice.



### HIGHLIGHTS

- Efficacy up to 143 Lumens/Watt Delivered
- 0-10 Volt Dimming, External Driver
- Aluminum Heat Sink/Extrusion
- Integral Volumetric 5" Lens
- 180 Degree Light Distribution
- 10 Year Warranty Complete System
- High Reflectance Coating
- Hinges & Latches from Both Sides
- Modernized Aesthetic
- Rapid Installation
- Fits Most Existing T8 & T12 Troffers-2x4, 2x2, 1x4
- Custom Sizing Available

### APPLICATIONS

- For Low and High Bay Installations



# TROFFER DOOR RETROFIT (TDR)

## EFFICACY

- Only top tier performance diodes for ultra-high Lumens/Watt
- Lowest Watts per Foot Candles Available

## THERMAL DISSIPATION

- The heat sink extrusion is made of 6063 T5 Aluminum with substantial fins & surface area for superior heat dissipation
- Patent pending Air Flow Cavity under LED PCB allows dissipated heat to leave the URS area
- Interior PCB Board is made of aluminum core and mechanically bonded to the aluminum extrusion heat sink

## OPTICS

- Integral Volumetric Lens transmits 91% of generated lumens (can be omitted to expose URS Light Bar)
- Suitable for most food processing applications
- The beam angle is 180 degrees for a wide distribution of light
- Glass Free

## SPECIFICATIONS

Suitability	Most Troffers-2x4, 2x2, 1x4
Warranty	10 Years Complete System
Expected Life	> 102,000 L90
Driver	External, 0-10 Volt Dimmable
System Input Wattage (driver dependent)	18-44 Watts
Efficacy (3500K)	143 Lumens/Watt (+/- 10%)
Voltage	100-277 Volts AC
Beam Angle	180
Integral Volumetric Diffuser	5" Lens Frosted, 91% Transmission Rate
Color Rendering Index (CRI)	81
Color Temperature	3500K, 4100K, or 5000K
Extrusion Material	6063 T5 Aluminum
Operating Temperature	-40F - 125F
Power Factor	0.99
Total Harmonic Distortion (THD)	< 9% (277 Volt)
Certifications	UL, DLC Premium, Lighting Facts, RoHS

## ORDERING INFORMATION: TROFFER DOOR RETROFIT (TDR)


Product Series	Size	Color Temp Options	System Input Power	Lumens/System	Options
LL-____-____-K-__					
	1x4	3500K	18	2455	ODIM
	2x2	4100K	22	2856	SDIM
	2x4	5000K	22	3183	DLEN
			26	3680	
			36	4878	
			44	5993	

EXAMPLE:  
LL-TDR-24-50K-44


All Linmore products are available with wireless controls, compatible with

**EASYFIT**  
by EnOcean


### Dimensions



22 1/4" x 45 7/8" x 2 1/2"



22 1/4" x 21 7/8" x 2 1/2"



10 1/4" X 45 7/8" x 2 1/2"

## INSTALLATION NOTES

- Installation Brackets and Trim Kit included
- Driver separate for installation inside troffer
- Troffer Door ships assembled with URS Light Bar and 5" lens

\*2x2' available in 18, 22, and 26 Watts only