

COMPLETE TROFFER FIXTURE (TRF)

Linmore LED Labs Complete Troffer Fixture (TRF) is the ultimate troffer fixture product line. The TRF is modern, aesthetic troffer and a serious energy play. The light engine of the TRF is Linmore's patent-pending URS Light Bar System combined with an external, dimmable driver. The amount of light, without glare, and the consistent distribution of light per watt of energy consumed is unmatched by any other troffer fixture. When the objective for a new troffer is ultra-low energy and a modern appeal, the Linmore TRF is the clear choice.



HIGHLIGHTS

- Efficacy up to 143 Lumens/Watt Delivered
- 0 -10 Volt Dimming, External Driver
- Aluminum Heat Sink/Extrusion
- Integral Volumetric 5" Lens
- 180 Degree Light Distribution
- Warranty: 14 Years Light Bar / 10 Years Driver
- High Reflectance Coating
- Modernized Aesthetic
- Rapid Installation
- Impact Resistant



COMPLETE TROFFER FIXTURE (TRF)

EFFICACY

- Only top tier performance diodes for ultra-high Lumens/Watt
- Lowest Watts per Foot Candles Available

THERMAL DISSIPATION

- The heat sink extrusion is made of 6063 T5 Aluminum with substantial fins & surface area for superior heat dissipation
- Patent pending Air Flow Cavity under LED PCB allows dissipated heat to leave the URS area
- Interior PCB Board is made of aluminum core and mechanically bonded to the aluminum extrusion heat sink

OPTICS

- Integral Volumetric Lens transmits 91% of generated lumens (can be omitted to expose URS Light Bar)
- Suitable for most food processing applications
- The beam angle is 180 degrees for a wide distribution of light
- Glass Free

Suitability	T-Bar Ceilings-2x4, 2x2, 1x4
Warranty	14 Years Light Bar / 10 Years Driver
Expected Life	> 102,000 L90
Driver	External, 0-10 Volt Dimmable
System Input Wattage (driver dependent)	15-44 Watts
Efficacy (3500K)	143 Lumens/Watt (+/- 10%)
Voltage	100-277 Volts AC
Beam Angle	180
Integral Volumetric 5" Lens	Frosted, 91% Transmission Rate
Color Rendering Index (CRI)	81
Color Temperature	3500K, 4100K, or 5000K
Extrusion Material	6063 T5 Aluminum
Operating Temperature	-40F - 125F
Power Factor	0.99
Total Harmonic Distortion (THD)	< 9% (277 Volt)
Certifications	DLC Premium, UL, Lighting Facts, RoHS


ORDERING INFORMATION: COMPLETE TROFFER FIXTURE

Product Series	Size	Color Temp	System Input Power	Lumens/System	Options
LL-____-__K-__					
	22 - 2x2'	35K-3500	18	2455	ODIM Outboard Dimmer Switch
	24 - 2x4'	41K-4100	22	3183	SDIM Step Dim Module For A-B Switching 33% - 66% - 100%
	14 - 1x4'	50K-5000	26	3680	DLEN Delete Lens
			36	4878	
			44	5693	


EXAMPLE:
LL-TRF-14-50K-44




Dimensions



23 7/8" x 47 7/8" X 2 1/2"



23 7/8" x 23 7/8" x 2 1/2"



11 3/4" X 47 7/8" X 2 1/2"

INSTALLATION NOTES

- Troffer Door ships assembled with URS Light Bar and 5" lens, and driver attached



Specifications are Subject to Change.

*2x2' available in 18, 22, and 26 Watts only